

|                                                 |                        |                                                     |
|-------------------------------------------------|------------------------|-----------------------------------------------------|
| LOC/DME I-ROW<br><b>109.9</b><br>Chan <b>36</b> | APP CRS<br><b>215°</b> | Rwy Ldg<br>TDZE <b>3633</b><br>Apt Elev <b>3671</b> |
|-------------------------------------------------|------------------------|-----------------------------------------------------|

ILS Z or LOC Z RWY 21  
ROSWELL AIR CENTER (ROW)

|                                                                                                                                                                                                                                                                                                                                                                             |        |                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------|
| ADF or DME required.                                                                                                                                                                                                                                                                                                                                                        | MALS R | MISSED APPROACH: Climb to 5000 then climbing right turn to 6000 on CME VORTAC R-195 to CME VORTAC and hold, continue climb-in-hold to 6000. |
| VDP NA when using Artesia altimeter setting. When local altimeter setting not received, use Artesia altimeter setting: increase DA to 3913 feet; increase all MDAs 80 feet and S-LOC 21 visibility Cat C/D ¾ SM and Circling visibility Cat D ¼ SM. For inop ALS when using Artesia altimeter setting, increase ILS all Cats visibility to ¾ SM and LOC Cats C/D to 1 ¾ SM. |        |                                                                                                                                             |

|                             |                                         |                                                |                               |                         |
|-----------------------------|-----------------------------------------|------------------------------------------------|-------------------------------|-------------------------|
| ATIS<br><b>128.45 306.2</b> | ROSWELL APP CON ★<br><b>119.6 239.0</b> | ROSWELL TOWER ★<br><b>118.5 (CTAF) 0 233.7</b> | GND CON<br><b>121.9 348.6</b> | UNICOM<br><b>122.95</b> |
|-----------------------------|-----------------------------------------|------------------------------------------------|-------------------------------|-------------------------|

