

WAAS CH 70402 W35A	APP CRS 350°	Rwy Ldg TDZE 3671 Apt Elev 3671
--	------------------------	---

RNAV (GPS) RWY 35

ROSWELL AIR CENTER (ROW)

RNP APCH - GPS.

▼



⚠

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.
When local altimeter setting not received, use ATS altimeter setting: increase LPV DA to 4001 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 4033 feet; increase all MDAs 80 feet and LNAV visibility Cat C ¼ SM and Circling visibility Cat D ¼ SM.
Baro-VNAV and VDP NA when using ATS altimeter setting.

MISSED APPROACH: Climb to 6000 direct HOGIG and hold.

ATIS 128.45 306.2	ROSWELL APP CON ★ 119.6 239.0	ROSWELL TOWER ★ 118.5 (CTAF) 0 233.7	GND CON 121.9 348.6	UNICOM 122.95
-----------------------------	---	--	-------------------------------	-------------------------



6000	HOGIG	KIGDE	5 NM Holding Pattern	
				
	1.3 NM to RW35	SIBPO	170° → 6000	
		350°	← 350°	
	1.3 NM	5400	GP 3.00° TCH 50	
	3.9 NM	6 NM		
CATEGORY	A	B	C	D
LPV DA	3921-3¼ 250 (300-¾)			
LNAV/VNAV DA	3953-1 282 (300-1)			
LNAV MDA	4120-1	449 (500-1)	4120-1⅜ 449 (500-1⅝)	4120-1½ 449 (500-1½)
CIRCLING	4140-1	469 (500-1)	4140-1½ 469 (500-1½)	4300-2 629 (700-2)