

SAN ANTONIO, TEXAS

WAAS CH 52296 W16A	APCH CRS 158°	Rwy ldg TDZE Arpt Elev	11,550 690 690
--------------------------	------------------	------------------------------	----------------------

(USAF)

RNAV (GPS) RWY 16

KELLY FLD (KSKF)

RNP APCH

- ▼ * When ALS inop, increase RVR to 40, vis to 3/4 miles.
** When ALS inop, increase RVR to 55, vis to 1 mile.
*** When ALS inop, increase CAT AB RVR to 55, and vis to 1 mile;
CAT CDE RVR to 60 vis to 1 1/8 miles.


ALSF-1

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct FTER and hold.

ATIS 120.45 273.5	SAN ANTONIO APP CON 118.05 353.5	KELLY TOWER 124.3 322.35	GND CON 121.8 289.4
----------------------	-------------------------------------	-----------------------------	------------------------

**** Circling not authorized
E of Rwy 16-34.

For uncompensated
BARO-VNAV systems,
LNAV/VNAV NA below -16°C
(3°F) or above 54°C (129°F).



EMERG SAFE ALT 100 NM 4200

FAMDO
3000

VGSI and descent angles not coincident (VGSI Angle 3.01/TCH 89).

GP 3.00°
TCH 57

ZILEN

2400

158°

EHUTU
2 NM to RWY 16

1360

1 NM to RWY 16

RWY 16

3.1 NM

2 NM

1500

3000

FITER

ELEV 690

158°

91

11,550 ± 100

0.33% DOWN

TWR

34

TDZE 690

CATEGORY	A	B	C	D	E
LPV DA*	890/24	200	(200-½)		
LNAV/VNAV DA**	1065/35	375	(400-¾)		
LNAV MDA***	1100/24 410 (500-½)	1100/40 410 (500-¾)			
CIRCLING****	1200-1 510 (600-1)	1280-1 590 (600-1)	1340-1¼ 650 (700-1¼)	1900-3 1210 (1300-3)	

HIRL all rwys

SAN ANTONIO, TEXAS

29°23'N - 98°35'W

KELLY FLD (KSKF)

Amdt 3 04SEP25

RNAV (GPS) RWY 16

SC-3, 01 OCT 2026 to 29 OCT 2026

SC-3, 01 OCT 2026 to 29 OCT 2026