

LOC/DME I-GWQ	APP CRS	28R	28L
<u>111.7</u>	284°	Rwy Ldg 11236	10275
Chan 54		TDZE 13	13
		Apt Elev 13	13

ILS or LOC RWY 28R
SAN FRANCISCO INTL (SFO)

RNAV 1-GPS or RADAR required for procedure entry.

- V** Circling NA to Rwy's 10L, 10R, 19L, and 19R. Circling Rwy 1L, 1R NA at night. LOC procedure NA during simultaneous operations. For inop ALS increase S-LOC 28R* Cot C/D visibility to 1 $\frac{1}{2}$ SM. Simultaneous approach authorized. Simultaneous operations require use of vertical guidance; maintain last assigned altitude until established on glideslope.


ALSF-2
Rwy 28R

MALSR
Rwy 28L

MISSED APPROACH: Climb to 3000 on SFO VOR/DME R-281 to VIKYU INT/SFO 12 DME and hold.

*Missed approach requires minimum climb of 350 feet per NM to 1900; if unable to meet climb gradient, see ILS or LOC RWY 28L.

D-ATIS 113.7 115.8 118.5	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8
-----------------------------	-------------------------------	------------------------------------	------------------



ELEV 13	D	TDZE 28R 13
HIRL all rwys		TDZE 28L 13
TDZL/RCLS Rwy 19L and 28R		
REIL Rwy 1L, 1R and 10L		

