




APP CRS	Rwy Ldg	11236
284°	TDZE	13
	Apt Elev	13


RNAV (RNP) Y RWY 28R

SAN FRANCISCO INTL (SFO)

RNP AR APCH, RF required.	ALSF-2	MISSED APPROACH: Climb to 3000 on track 284° to VIKYU and hold. * Missed approach requires minimum climb of 250 feet per NM to 1600. # Missed approach requires minimum climb of 350 feet per NM to 2100.
▼ For uncompensated Baro-VNAV systems, procedure NA below 3°C or above 54°C. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 4000 and RNP 0.30 all Cats visibility to RVR 4500.		

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8
------------------------------	-------------------------------	------------------------------------	------------------



3000 ↑ tr 284°	VIKYU	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 68)			GUTTS
					
		FABLA	JOSUF	DONNG	3400
		743	1264	1800	
					
		2.1 NM	1.6 NM	1.7 NM	5.2 NM
					GP 3.00° TCH 55
CATEGORY		A	B	C	D
RNP 0.11 DA*			263/24	250 (300-½)	
RNP 0.30 DA#			326/24	313 (400-½)	

AUTHORIZATION REQUIRED