



WAAS CH 53533 W19B	APP CRS 194°	Rwy Ldg TDZE 11 Apt Elev 13
--	------------------------	---

RNAV (GPS) Y RWY 19R

SAN FRANCISCO INTL (SFO)

RNP APCH-GPS. ▼ ⚠ LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 4°C or above 54°C. Simultaneous approach authorized. Simultaneous operations require use of vertical guidance; maintain last assigned altitude until established on glidepath. Simultaneous approach NA below 12°C (52°F).	MISSED APPROACH: Climb to 1540 then climbing right turn to 3000 direct THHEO and hold.
--	--

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8
-------------------------------------	--------------------------------------	---	-------------------------



CATEGORY	A	B	C	D
LPV DA	1005-4 994 (1000-4)			
LNAV/VNAV DA	878-2 1/2 867 (900-2 1/2)			
LNAV MDA	1320-1 1/4 1309 (1400-1 1/4)	1320-1 1/2 1309 (1400-1 1/2)	1320-3	1309 (1400-3)

