

WAAS
CH **73005**
W12A

APP CRS
126°

Rwy Ldg
TDZE **3963**
Apt Elev **3967**

SCOTTSLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BFTF)

RNAV (GPS) RWY 12

26190

RNP APCH - GPS

When local altimeter setting not received, use AIA altimeter setting: increase LPV DA to 4304 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 4431 feet and all visibilities ¼ SM; increase all MDAs 100 feet and LNAV visibility Cats B/C ¼ SM, LNAV visibility Cat D ½ SM and Circling all Cats visibilities ½ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 SM and LNAV Cats C/D visibility to 2 SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. Baro-VNAV and VDP NA when using AIA altimeter setting.

MALSR

MISSED APPROACH:
Climb to 6700 direct HAKAB and hold.

ASOS 121.025	DENVER CENTER 127.95 338.2	UNICOM 123.0 (CTAF) 0
------------------------	--------------------------------------	---------------------------------

Procedure NA for arrivals at ALBIN V81 southwest bound and arrivals at SPONS V81-V169 northbound.

ELEV 3967	D	TDZE 3963
-----------	----------	-----------

7 NM Holding Pattern		LEDSE		CAPGA		RWY 12						
6900		305°		125°		126°						
GP 3.00°		TCH 57		5700		2.1 NM to RWY 12						
		6.1 NM		3.1 NM		2.1 NM						
CATEGORY	A	B	C	D								
LPV DA	4213-½ 250 (300-½)											
LNAV/VNAV DA	4340-¾ 377 (400-¾)											
LNAV MDA	4700-½ 737 (800-½)		4700-1½ 737 (800-1½)		4700-1¾ 737 (800-1¾)							
CIRCLING	4700-1 733 (800-1)		4700-2 733 (800-2)		4740-2½ 773 (800-2½)							

SCOTTSLUFF, NEBRASKA
Amdt 1B 09JUL26

SCOTTSLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BFTF)
41°52'N-103°36' W

RNAV (GPS) RWY 12