

LOC FSD
109.9

APP CRS
030°

Rwy Ldg
TDZE
Apt Elev
8999
1424
1430

ILS or LOC RWY 3

JOE FOSS FLD (FSD)

ADF or RADAR required.


⚠
ASR
-30°C

For inop ALS, increase S-LOC 3 Cats C/D visibility to 1½ SM,
and S-LOC 3 MAREY fix minimums Cats C/D to 1¾ SM.

MALSR
⚠

MISSED APPROACH: Climb to 3400 then
left turn direct FSD VORTAC and hold.

ATIS 126.6	SIoux FALLS APP CON* 125.8 284.725	SIoux FALLS TOWER* 118.3 (CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95
----------------------	--	---	-------------------------------	-------------------------



One Minute Holding Pattern				
FS LOM ROKKY RADAR				
MAREY INT				
3400				
3305				
2100				
3.7 NM				
2 NM				
CATEGORY	A	B	C	D
S-ILS 3	1674/24 250 (300-½)			
S-LOC 3	2100/24	676 (700-½)	2100-1½	676 (700-1½)
CIRCLING	2100-1	670 (700-1)	2100-1¾ 670 (700-1¾)	2200-2½ 770 (800-2½)
MAREY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 3	1940/24	516 (600-½)	1940/55	516 (600-1)
CIRCLING	1980-1	550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)

