

(ENDED2.ENDED) 25219

AL-416 (FAA)

TAMPA INTL (TPA)
TAMPA, FLORIDA

ENDED TWO DEPARTURE (RNAV)


TAMPA DEP CON
118.8 239.3
D-ATIS
128.475
CLNC DEL
133.6
CPDLC
GND CON
121.7 269.4
TAMPA TOWER
119.5 269.4

RNAV 1 - DME/DME/IRU or GPS required.
RADAR required

TOP ALTITUDE:
6000

TAKEOFF MINIMUMS

Rwys 1L/R, 19R, 28: Standard.
Rwy 10: Standard with minimum climb of 240'/NM to 800.
Rwy 19L: Standard with minimum climb of 230'/NM to 300.



NOTE: Jet aircraft only.

NOTE: Chart not to scale. (CONTINUED ON FOLLOWING PAGE)

ENDED TWO DEPARTURE (RNAV)

(ENDED2.ENDED) 16MAY24

TAMPA, FLORIDA
TAMPA INTL (TPA)

SE-3, 01 OCT 2026 to 29 OCT 2026

SE-3, 01 OCT 2026 to 29 OCT 2026



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 1L/R: Climb on heading 007° to 540, then on heading 003°
for vectors to ENDED thence

TAKEOFF RUNWAY 10: Climb on heading 097° to 540, then on heading 093°
for vectors to ENDED thence

TAKEOFF RUNWAY 19L: Climb on heading 187° to 540, then on heading 213°
for vectors to ENDED thence

TAKEOFF RUNWAY 19R: Climb on heading 187° to 540, then on heading 203°
for vectors to ENDED thence

TAKEOFF RUNWAY 28: Climb on heading 277° to 540, then on heading 273°
for vectors to ENDED thence

. . . . on track 357° to LACEN. Maintain 6000. Expect clearance to filed altitude
within ten minutes after departure.

SE-3, 01 OCT 2026 to 29 OCT 2026

SE-3, 01 OCT 2026 to 29 OCT 2026