

TAMPA, FLORIDA

ILS or LOC RWY 23

LOC I-GBZ
111.7

APCH CRS
229°

Rwy Idg **11,421**
TDZE **14**
Arpt Elev **14**

AL-418 [USAF]

MACDILL AFB (KMCF)

RADAR or DME required.

* When ALS inop, increase RVR to 40, vis to ¼ mile.

** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 ½ miles.

ALSF-1

MISSED APPROACH: Climb to 1600 via MCF R-223 to MILNE and hold.
RNAV or ATC RADAR required for missed approach.

ATIS
133.825 270.1

TAMPA APP CON
124.95 354.0

TOWER
120.175 294.7

GND CON
118.575 275.8

*** Circling not authorized NW of Rwy 5-23.

WARNING:
Use extreme caution
PETER O. KNIGHT arpt
4 NM NE of MACDILL AFB

Expect RADAR vectors around
St. Petersburg landmass for
noise abatement, unless
otherwise requested by pilot.

LOCALIZER 111.7
I-GBZ
LOC offset 2.65°

CAUTION:
LOC course offset 2.68° from
the extended rwy centerline
and intersects the rwy centerline
1346' after the DA.

EMERG SAFE ALT 100 NM 3000

CATEGORY	A	B	C	D	E
S-ILS 23 *	264/24		250	(300-½)	
S-LOC 23 **	440/24 426 (500-½)		440/40 426 (500-¾)		
*** CIRCLING	500-1 486 (500-1)	540-1 526 (600-1)	540-1½ 526 (600-1½)	580-2 566 (600-2)	1020-3 1006 (1100-3)

ELEV 14

TDZE 14

HIRL Rwy 5-23

FAF to MAP 4.3 NM

Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

SE-3, 01 OCT 2026 to 29 OCT 2026

SE-3, 01 OCT 2026 to 29 OCT 2026

TAMPA, FLORIDA

27°51'N-82°31'W

MACDILL AFB (KMCF)

Amtd 2 10AUG23

ILS or LOC RWY 23