

WAAS Ch 93899 W04A	APP CRS 040°	Rwy Ldg 6602 TDZE 360 Apt Elev 390
--	------------------------	---

RNAV (GPS) RWY 4

TEXARKANA RGNL-WEBB FLD (TXK)


▼

⚠

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). When local altimeter setting not received, use J Lynn Helms Sevier County altimeter setting and increase all DA/MDA 100 feet, increase LPV and LNAV/VNAV all Cats visibility ¼ mile, LNAV and Circling Cat C and D visibility ½ mile. Baro-VNAV NA when using J Lynn Helms Sevier County altimeter setting.

MISSED APPROACH:
Climb to 2100 direct WORPA and hold.

ATIS 120.2	FORT WORTH CENTER 123.925 269.475	TEXARKANA TOWER ★ 123.875 (CTAF) 0 235.625	GND CON 119.225
----------------------	---	--	---------------------------



ELEV 390

D TDZE 360

Procedure Turn NA

GP 3.00°
TCH 52

YOBUG

PECIP

2100

WORPA

2000

2000

6 NM

5 NM

RW04

CATEGORY	A	B	C	D
LPV DA	613-1 253 (300-1)			
LNAV/VNAV DA	866-1¾ 506 (500-1¾)			
LNAV MDA	900-1 540 (600-1)	900-1½ 540 (600-1½)	900-1¾ 540 (600-1¾)	
CIRCLING	900-1¾ 510 (600-1¾)	1000-2 610 (700-2)	1080-2¼ 690 (700-2¼)	

MIRL Rwy 13-31 0

HIRL Rwy 4-22 0

TWR

13

31

2

45

5200 X 100

6602 X 150

0.7% UP

0.5% UP

040°

SC-1, 01 OCT 2026 to 29 OCT 2026

SC-1, 01 OCT 2026 to 29 OCT 2026