

WAAS CH 65934 W03A	APP CRS 035°	Rwy Ldg TDZE 1078 Apt Elev 1078
--	------------------------	---

RNAV (GPS) RWY 3

TOPEKA RGNL (F0E)


RNP APCH - GPS.

▼

Baro-VNAV NA when using Philip Billard Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Philip Billard Muni altimeter setting and increase all DA 45 feet and all MDA 60 feet, increase LPV all Cats and LNAV/VNAV all Cats visibility ¼ mile, LNAV Cat C/D and Circling Cat D - visibilities ¼ mile.

MISSED APPROACH:
Climb to 3000 direct
VAJEG and hold.

ATIS 128.25	KANSAS CITY CENTER 123.8 343.7	FORBES TOWER★ 120.8 (CTAF) 0 340.2	GND CON 118.425 275.8	UNICOM 122.95
-----------------------	--	--	---------------------------------	-------------------------



4 NM Holding Pattern	IDJOP	3000	215°	035°	035°	2700	ANWOV	HOVR 1.4 NM to RW03	RW03	*1560	7 NM	3.6 NM	1.4 NM
GP 3.00° TCH 47													
CATEGORY	A	B	C	D									
LPV DA		1328-¾	250 (300-¾)										
LNAV/VNAV DA		1363-⅞	285 (300-⅞)										
LNAV MDA	1460-1	382 (400-1)	1460-1½	382 (400-1½)									
CIRCLING	1520-1 442 (500-1)	1580-1 502 (600-1)	1580-1½ 502 (600-1½)	1700-2 622 (700-2)									

