

WAAS CH 86405 W20A	APP CRS 204°	Rwy Ldg TDZE Apt Elev	8919 270 270
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20
WESTFIELD-BARNES RGNL (BAF)



 -20°C

Baro-VNAV NA when using Bradley Int'l altimeter setting. For uncompensated Baro-VNAV systems, VNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Bradley Int'l altimeter setting and increase LPV DA to 561; VNAV/VNAV DA to 996 and increase all Cats visibility to 2¼; all MDA 60 feet and LNAV/Cats B, C, D and E visibility to 1¼. For inoperative MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 2½, LNAV/Cat E visibility to 1½. Night landing: Rwy 15 NA.

MALSR



MISSED APPROACH:
Climb to 1700 then
climbing right turn to
4000 direct CTR
VOR/DME and hold.

ATIS 127.1 263.15	BRADLEY APP CON 125.35 281.5	WESTFIELD TOWER ★ 125.075 (CTAF) 0 251.1	GND CON 121.7 289.4
--	---	---	--

