



BAF VORTAC	APP CRS	Rwy Ldg	9000
113.0	025°	TDZE	264
Chan 77		Apt Elev	270

VOR or TACAN RWY 2
WESTFIELD-BARNES RGNL (BAF')

RADAR required for procedure entry.		MISSED APPROACH: Climb to 3000 on BAF VORTAC R-028 to KLYDE INT/BAF 6 DME and hold, continue climb-in-hold to 3000.
Rwy 2 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use BDL altimeter setting and increase all MDAs 60 feet and S-2 visibility Cat C/D/E ¼ SM. VDP NA when using BDL altimeter setting. Circling Rwy 15 NA at night.		

ATIS 127.1 263.15	BRADLEY APP CON 125.35 281.5	WESTFIELD TOWER ★ 125.075 (CTAF) 0 251.1	GND CON 121.7 289.4
----------------------	---------------------------------	---	------------------------



NUTTN INT BAF 11.6 RADAR 3000			VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 50).			3000 BAF R-028 KLYDE INT		
025° 2100			DECAR INT BAF 6.6 RADAR			JAGON BAF 1 BAF VORTAC		
5 NM			3.02° TCH 43			3.8 NM		
1.8 NM								
CATEGORY	A	B	C	D	E			
S-2	900-1	636 (700-1)	900-1¾ 636 (700-1¾)					
CIRCLING	1160-1¼	890 (900-1¼)	1160-2¾ 890 (900-2¾)		1660-3	1390 (1400-3)		

