

WAAS CH 86605 W30A	APP CRS 301°	Rwy Ldg TDZE 405 Apt Elev 410
--	------------------------	---

RNAV (GPS) Y RWY 30
TRI-CITIES (PSC)


RNP APCH - GPS.

Baro-VNAV and VDP NA when using HRI altimeter setting. Rwy 30 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. When local altimeter setting not received, use HRI altimeter setting: increase LPV DA to 750 feet; increase LNAV/VNAV DA to 888 feet and all visibilities ¼ SM, and increase all MDAs 100 feet and LNAV and Circling visibility Cats C and D ¼ SM.

MALSF

MISSED APPROACH: Climb to 900 then climbing left turn to 5200 direct PAIDS and hold, continue climb-in-hold to 5200.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 285.55	GND CON 121.8	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



ELEV 410 **D** TDZE 405

REIL Rwy 3L and 12 **1**

MIRL Rwy 12-30 **1**

HIRL Rwy 3L-21R **1**

	900	5200	PAIDS				
				ACWEW	IHAYO	4 NM Holding Pattern	
				PASBE 3 NM to RW30			
				1.3 NM to RW30			
				1400	2200		
				1.3 NM	1.6 NM	2.5 NM	6 NM
CATEGORY	A	B	C	D			
LPV DA	655-¾		250 (300-¾)				
LNAV/VNAV DA	793-7/8		388 (400-7/8)				
LNAV MDA	880-¾		475 (500-¾)		880-1½		475 (500-1½)
CIRCLING	900-1		940-1		1040-1¾		1100-2¼
	490 (500-1)		530 (600-1)		630 (700-1¾)		690 (700-2¼)

NW-1, 01 OCT 2026 to 29 OCT 2026

NW-1, 01 OCT 2026 to 29 OCT 2026