

LOC/DME I-JAC 109.1 Chan 28	APP CRS 187°	Rwy Ldg 6300 TDZE 6451 Apt Elev 6451
---	------------------------	---

ILS Y or LOC Y RWY 19
JACKSON HOLE (JAC)

RADAR required for procedure entry at MOSSS.

T Circling NA for Cats A, B and C east of Rwy 1-19. Circling NA for
A Cat D. For inop ALS, increase SOSUE fix minimums S-LOC 19 Cats
❄ -21°C C and D visibility to 2½ SM. For inop ALS, increase S-LOC Cat
 C and D visibility to 3 SM.



MALS



MISSED APPROACH: Climb to 14000 on JAC VOR/DME R-192 to KICNE INT/JAC VOR/DME 26.6 DME and hold, continue climb-in-hold to 14000.

D-ATIS 120.625	SALT LAKE CENTER 133.25 285.6	JACKSON TOWER ★ 118.075 (CTAF) 0	GND CON 124.55	UNICOM 122.95
-------------------	----------------------------------	-------------------------------------	-------------------	------------------

MISSED APCH FIX




LOCALIZER 109.1
I-JAC :--
Chan 28

Use I-JAC DME when on the localizer course.

173

ELEV 6451	D	TDZE 6451
-----------	----------	-----------



RCLS Rwy 1-19 **L**
HIRL Rwy 1-19 **L**

FAF to MAP 9.7 NM					
Knots	60	90	120	150	180
Min:Sec	9:42	6:28	4:51	3:53	3:14

14000 ↑ JAC R-192	KICNE △	Use I-JAC DME when on the localizer course.		QUIRT I-JAC 17.3 DWN 12.2	Remain within 10 NM
CATEGORY	A	B	C	D	
S-ILS 19	7077-1½ 626 (700-1½)				
S-LOC 19	7540/55 1089 (1100-1)	7540-1¼ 1089 (1100-1¼)	7540-2½ 1089 (1100-2½)		
CIRCLING	7540-1¼ 1089 (1100-1¼)	7540-1½ 1089 (1100-1½)	7540-3 1089 (1100-3)	NA	
SOSUE FIX MINIMUMS (DME REQUIRED)					
S-LOC 19	7300/40 849 (900-¾)	7300/55 849 (900-1)	7300-2 849 (900-2)		
CIRCLING	7300-1¼ 849 (900-1¼)		7400-2¾ 949 (1000-2¾)	NA	