

WAAS CH 56523 W12A	APP CRS 118°	Rwy Ldg TDZE Apt Elev	4400 3294 3298
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 12


CHADRON MUNI (CDR)

⚠

Baro-VNAV NA when using Pine Ridge altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Pine Ridge altimeter setting and increase all DA 70 feet and all MDA 80 feet; increase LPV all Cats visibility ½ mile, LNAV/VNAV all Cats visibility ¼ mile, and Circling Cat C visibility ¼ mile.

MISSED APPROACH:
Climb to 5900 direct
ECOPO and hold.

ASOS 118.05	DENVER CENTER 127.95 338.2	UNICOM 122.8 (CTAF) 0
-----------------------	--------------------------------------	---------------------------------



ELEV 3298	D	TDZE 3294
-----------	----------	-----------

7 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 29).

5900 ECOPO

6300 ← 298°
118° →

GP 3.00°
TCH 42

CABAX

AJIRE 4500

IGOKY 2.1 NM to RW12

*LNAV only

4500

*4000

RW12

7.5 NM

1.6 NM

2.1 NM

CATEGORY	A	B	C	D
LPV DA	3544-1	250 (300-1)		NA
LNAV/VNAV DA	3719-1½	425 (500-1½)		NA
LNAV MDA	3720-1	426 (500-1)	3720-1¼ 426 (500-1¼)	NA
CIRCLING	3820-1 522 (600-1)	3920-1 622 (700-1)	3920-1¾ 622 (700-1¾)	NA

