

ILS or LOC RWY 22

LOC I-CVS 109.7	APCH CRS 218°	Rwy Idg 10,001 TDZE 4295 Arprt Elev 4295	[USAF]
Missed approach requires use of RNAV or RADAR monitoring.			CANNON AFB (KCVS)

▼ * When ALS inop, increase RVR to 40 and vis to ¾ miles.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 ½ miles.

ATIS 119.1 269.9	APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8
----------------------------	---------------------------------	------------------------------	-------------------------------

CAUTION:
 1. ILS Rwy 22 Height Group 4 WCH 19 feet.

6000 CVS R-220	JEBES CVS 6	7000	CLINK CVS 12
-------------------	----------------	------	-----------------

EMERG SAFE ALT 100 NM 8000

6000 CVS R-220	JEBES CVS 6	7000	CLINK CVS 12
-------------------	----------------	------	-----------------

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 38).

OPKUE CVS 5.1	218°	6000	HEKDI CVS 12
------------------	------	------	-----------------

GS 3.00° TCH 44

CATEGORY	A	B	C	D	E
S-ILS 22*	4495/24				
S-LOC 22**	4720/24 425 (500-½)		4720/40 425 (500-¾)		
CIRCLING	4840-1 545 (600-1)		4860-1 ½ 565 (600-1 ½) 5000-2 ¼ 705 (800-2 ¼) 5020-2 ½ 725 (800-2 ½)		

HIRL all rwys

FAF to MAP 4 NM

Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:20

SW-1, 01 OCT 2026 to 29 OCT 2026

SW-1, 01 OCT 2026 to 29 OCT 2026