

LOC/DME I-DSO	APP CRS	Rwy Ldg	8021
109.9	041°	TDZE	389
Chan 36		Apt Elev	422

ILS or LOC RWY 4

EVANSVILLE RGNL (EVV)

⚠

ASR

Circling Rwy 9 NA at night.

MISSED APPROACH: Climb to 1500 then climbing left turn to 2500 direct PXV VORTAC and hold.

ATIS	EVANSVILLE APP CON ★	EVANSVILLE TOWER ★	GND CON	UNICOM
120.2	124.025 290.9	118.7(CTAF) 257.8	121.9	122.95

Procedure NA for arrival on PXV VORTAC
airway radials 043 CW 081.

LOCALIZER 109.9
I-DSO
Chan 36

OWENSBORO
OWB
108.65
Chan 23(Y)

108.65 OWB
Chan 23(Y)

IAF
POCKET CITY
113.3 PXV
Chan 80

KECEG INT
I-DSO 2.2

WIDIT INT
I-DSO 4.8

HUGMU INT
I-DSO 9.3
PXV 5.3

(IF)

(IAF)
ARLUV
I-DSO 13

R-237 057°
R-141 237°
R-098
R-314
R-308
R-298

2000 098° (5.3)
2000 041° (4.5)
2000 041° (3.8)

MSA PXV 25 NM
2500

1500

2500

PXV

HUGMU INT
I-DSO 9.3

WIDIT INT
I-DSO 4.8

2000

041°

2000

1180

KECEG INT
I-DSO 2.2

I-DSO DME ANTENNA

I-DSO 1.2

I-DSO 0.2

GS 3.00°
TCH 49

4.5 NM

2.6 NM

1 NM

1.4 NM

ELEV 422

TDZE 389

HIRL Rws 4-22 and 18-36

REIL Rws 4, 18, and 36

MIRL Rwy 9-27

81

3497

6

4286

36

041°

TWR

8021 X 150

0.3% UP

0.3% DOWN

27

75

CATEGORY	A	B	C	D
S-ILS 4		589-3/4	200 (200-3/4)	
S-LOC 4	1180-1 791 (800-1)	1180-1 1/4 791 (800-1 1/4)	1180-2 1/2	791 (800-2 1/2)
CIRCLING	1180-1 758 (800-1)	1180-1 1/4 758 (800-1 1/4)	1180-2 1/2	758 (800-2 1/2)
KECEG FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 4	880-1	491 (500-1)	880-1 3/8	491 (500-1 3/8)
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1 3/4 618 (700-1 3/4)	1040-2 618 (700-2)

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

EVANSVILLE, INDIANA

Amtd 5 25DEC25

38°02'N-87°32'W

EVANSVILLE RGNL (EVV)

ILS or LOC RWY 4