

WAAS CH 77623 W30A	APP CRS 301°	Rwy Ldg TDZE 293 Apt Elev 293
--	------------------------	---

RNAV (GPS) RWY 30

VISALIA MUNI (VIS)

RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 SM, and LNAV Cats C/D to 1 SM.

MALSR



MISSED APPROACH: Climb to 3000 direct INOC and on track 267° to LATON and hold, continue climb-in-hold to 3000.

AWOS-3PT 119.925	FRESNO APP CON 118.5	CLNC DEL 118.5	UNICOM 123.05 (CTAF) 
----------------------------	--------------------------------	--------------------------	--

ELEV 293	D	TDZE 293
----------	----------	----------

3000	INOC	tr 267°	LATON	PANES	4 NM Holding Pattern
			HOTLI 1.5 NM to RW30	2000	
			820	301°	16000
			1.5 NM	3.7 NM	2900
				5.9 NM	GP 3.00°
					TCH 53
CATEGORY	A	B	C	D	
LPV DA	500-1½ 207 (300-½)				
LNAV/VNAV DA	656-5⁄8 363 (400-5⁄8)				
LNAV MDA	660-½ 367 (400-½)		660-5⁄8 367 (400-5⁄8)		
CIRCLING	740-1 447 (500-1)	760-1 467 (500-1)	760-1½ 467 (500-1½)	940-2 647 (700-2)	

VISALIA, CALIFORNIA

Amtd 2A 19MAR26

36°19'N-119°24'W

RNAV (GPS) RWY 30

VISALIA MUNI (VIS)