

WAAS CH 65613 W20A	APP CRS 199°	Rwy Ldg TDZE 1262 Apt Elev 1268
--	------------------------	---



RNAV (GPS) RWY 20
SPRINGFIELD-BRANSON NTL (SGT')

⚠ DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F).
Baro-VNAV and VDP NA when using Monett altimeter setting.
Inoperative table does not apply to LNAV/VNAV all Cats and LNAV Cat C.
When local altimeter setting not received, use Monett altimeter setting and increase all DAs 90 feet and increase all MDAs 100 feet, increase LPV visibility all Cats ¼ mile, increase LNAV/VNAV all Cats ¼ mile, increase LNAV Cats C and D ¼ mile, increase Circling Cat C ¼ mile.

MALS
Ⓜ =

MISSED APPROACH: Climb to 3000 direct AWAKE and hold.

ATIS 135.125	SPRINGFIELD APP CON 124.95 290.5	SPRINGFIELD TOWER 119.9 257.8	GND CON 121.9 251.15
------------------------	--	---	--------------------------------



3000	AWAKE	FANDR	INOYU	4 NM Holding Pattern
*LNAV only	*1.5 NM to RW20			
	1.5 NM	3.7 NM	6.3 NM	
CATEGORY	A	B	C	D
LPV DA	1531-1	269 (300-1)		
LNAV/VNAV DA	1656-1½	394 (400-1½)		
LNAV MDA	1780-¾ 518 (600-¾)	1780-1½ 518 (600-1½)	1780-1¾ 518 (600-1¾)	
CIRCLING	1780-1 512 (600-1)	1820-1 552 (600-1)	1820-1½ 552 (600-1½)	1920-2 652 (700-2)

NC-3, 01 OCT 2026 to 29 OCT 2026

NC-3, 01 OCT 2026 to 29 OCT 2026