



WAAS CH 58020 W19A	APP CRS 189°	Rwy Ldg TDZE Apt Elev	7000 1218 1226
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 19
AKRON-CANTON RGNL (CAK)

 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). DME/DME RNP-0.3 NA. ** RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 3000 direct HOMEV and on track 184° to BSV VOR/DME and hold.
---	---	--

ATIS 121.05	CLEVELAND APP CON★ 125.5 269.25	AKRON-CANTON TOWER 134.75 279.575	GND CON 121.7 348.6
-----------------------	---	---	-------------------------------

Holding not required for arrivals on ACO VOR/DME airway radials 347 CW 185.



3000	HOMEV	BSV	OXESE	BUKIN	Procedure Turn NA
↑		tr 184°		2800	
* LNAV only					
* 1.4 NM to RWY 19					
GP 3.00° TCH 53					
CATEGORY	A	B	C	D	
LPV DA **	1418/24 200 (200-½)				
LNAV/VNAV DA	1753-1½ 535 (600-1½)				
LNAV MDA	1700/24	482 (500-½)	1700/40 482 (500-¾)	1700/50 482 (500-1)	
CIRCLING	1760-1	534 (600-1)	1780-1½ 554 (600-1½)	1800-2 574 (600-2)	