

LOC I-FFV	APP CRS	Rwy Ldg
111.3	139°	7540
		TDZE
		23
		Apt Elev
		30

ILS or LOC RWY 14

SARASOTA/BRADENTON INTL (SRQ)

DME or RADAR required for LOC only.

When control tower closed, S-ILS 14 Minimums NA; increase S-LOC 14 Cats A and B and ETIGY Fix Minimums S-LOC 14 all Cats visibility to 1 mile. When control tower closed, inop table does not apply to S-LOC 14 Cats A and B and ETIGY Fix Minimums S-LOC 14 all Cats.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 on SRQ VOR/DME R-118 to MURDO INT/SRQ 13.6 DME and hold.

ATIS	TAMPA APP CON	SARASOTA TOWER★	GND CON	UNICOM
124.375	119.65 353.575	120.1(CTAF) 256.8	121.9 273.6	122.95

ELEV 30 D TDZE 23

REIL Rwy 22 1
HIRL Rwy 14-32 and 4-22 1

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

One Minute Holding Pattern				
FRUGL SRQ 5.8 RADAR				
2000 ← 319° → 2000				
GS 3.00° TCH 54				
ETIGY SRQ 1.3				
*500				
4.5 NM 1.5 NM				
CATEGORY	A	B	C	D
S-ILS 14	223-½ 200 (200-½)			
S-LOC 14	500-½	477 (500-½)	500-1	477 (500-1)
CIRCLING	500-1	470 (500-1)	600-1½	600-2
ETIGY FIX MINIMUMS				
S-LOC 14	360-½ 337 (400-½)			
CIRCLING	500-1	470 (500-1)	600-1½	600-2
570 (600-½) 570 (600-2)				

SARASOTA/BRADENTON, FLORIDA

Amdt 6D 04NOV21

27°24'N-82°33'W

SARASOTA/BRADENTON INTL (SRQ)

ILS or LOC RWY 14