

APP CRS
186°

Rwy Ldg **11000**
TDZE **875**
Apt Elev **896**

RNAV (RNP) Z RWY 18C

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP AR APCH - GPS. Authorization required. From JEKEL or LTYER: RF.


MALSRL



MISSED APPROACH: Climb to 3000 direct JITEV and on track 181° to ZIRKE and hold.

 For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to 1 1/2 SM. Simultaneous approach authorized.


D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	GND CON 121.7
--------------------------	--	---	-------------------------



ELEV 896

D

TDZE 875



3000


JITEV

tr 181°

ZIRKE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

See planview for multiple IF locations.



WUTVU
2500
186°
2500
RW18C
4.9 NM
GP 3.00°
TCH 55

CATEGORY	A	B	C	D
RNP 0.15 DA		1190/24	315 (300-1/2)	
RNP 0.30 DA		1389/55	514 (500-1)	

AUTHORIZATION REQUIRED

SE-1, 01 OCT 2026 to 29 OCT 2026

SE-1, 01 OCT 2026 to 29 OCT 2026