RNAV (RNP) Z RWY 9

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

APP CRS	Rwy Ldg	11640
096°	TDZE	883
	Apt Elev	896

RNP AR APCH - GPS. Authorization required. From FLOTT or IDULE: RF.

For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 3000 direct BLOCK and on track 138° to CALIF and hold.

D-ATIS	CINCINNATI APP CON	CINCINNATI TOWER	GND CON
134.375	119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	121.7

MISSED APCH FIX

4 NM

111°

291°

CALIF

(IAF) ACHOO 7000 210K

3500 138° (12.7)

(IAF) BABGE 8000

3500 124° (14)

5000 277° (3.1)

HAPON

(IF) IDULE 6000 210K

2500 (8.2)

(IF) SEMSE

(FAF) KAVME

3500 096° (4.8)

(IAF) JADOP

2500 096° (3.3)

2500 (8.2)

096° (4.9)

RW09

BLOCK

138° (10)

MSA RW09 25 NM

3000

3500 058° (13.8)

(IAF) CALFS 8000

(IF) FLOTT 6000 210K

GEHDI

5000 276° (3.1)

ELEV 896 D TDZE 883

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

3000	BLOCK	tr 138°	CALIF

KAVME

2500

2500

096°

RW09

GP 3.00°

TCH 52

See planview for multiple IF locations.

4.9 NM

CATEGORY	A	B	C	D
RNP 0.18 DA		1205/26	322 (400-½)	
RNP 0.30 DA		1275/35	392 (400-⅝)	

AUTHORIZATION REQUIRED

18R

18C

18L

8000 X 150

10000 X 150

12001 X 150

0.3% DOWN

6% UP

36L

27

TWR

096°

36C

36R

HIRL all rwys

TDZL/RCLS all rwys except 27

SE-1, 01 OCT 2026 to 29 OCT 2026

SE-1, 01 OCT 2026 to 29 OCT 2026