

WAAS CH 40103 W18A	APP CRS 186°	Rwy Ldg 10000 TDZE 889 Apt Elev 896
--	------------------------	--

RNAV (GPS) Y RWY 18L
CINCINNATI/NORTHERN KENTUCKY INTL (CVG)


RNP APCH - GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats and LNAV Cat C and D visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 3000 direct LAPER and on track 136° to FLM VOR/DME and hold.

D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C)	GND CON 121.7
--------------------------	--	---	-------------------------



SE-1, 01 OCT 2026 to 29 OCT 2026

ELEV 896 TDZE 889

HIRL all rws
TDZ/L RCLS all rws except 27

CATEGORY	A	B	C	D
LPV DA	1089/18	200 (200-½)		
LNAV/VNAV DA	1360/50	471 (500-1)		
LNAV MDA	1360/24	471 (500-½)	1360/50	471 (500-1)
CIRCLING	1460-1	564 (600-1)	1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)