

WAAS CH 86999 W02A	APP CRS 016°	Rwy Ldg TDZE Apt Elev 5600 7 13
--	------------------------	---

RNAV (GPS) RWY 2

TWEED/NEW HAVEN (HVN)

RNP APCH - GPS.

⚠

When local altimeter setting not received, use Long Island Mac Arthur altimeter setting: increase LPV DA to 375 feet; increase LNAV/VNAV DA to 446 feet and all visibilities to RVR 5000; increase all MDAs 100 feet and LNAV visibility Cat C/D to RVR 6000 and Circling visibility Cat C/D ¼ SM. For inop ALS when using Long Island Mac Arthur altimeter setting, increase LPV visibility all Cats to RVR 5500. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. Night landing: Rwy 14, 32 NA. Rwy 2 helicopter visibility reduction below RVR 4000 NA. Baro-VNAV and VDP NA when using Long Island Mac Arthur altimeter setting. For inop ALS, increase LPV all Cats visibility to RVR 4500.

MALSF

MISSED APPROACH:
Climb to 600 then
climbing right turn to
2000 direct MAD
VOR/DME and hold.

ATIS 133.65	NEW YORK APP CON 124.075 343.65	NEW HAVEN TOWER★ 124.8 (CTAF)	GND CON 121.7	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------

