WAAS	APP CRS	Rwy Ldg	5255
CH 61112	156°	TDZE	54
W15A		Apt Elev	54

RNAV (GPS) RWY 15
CAPE COD GATEWAY (HYA)

RNP APCH - GPS.


T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 39°C. When local altimeter setting not received, use Chatham altimeter setting: increase LPV DA to 286 feet; increase LNAV/VNAV DA to 601 feet, visibility all Cats to RVR 6000; increase all MDAs 40 feet, LNAV visibility Cats C and D ⅛ SM, and Circling visibility Cats C and D ¼ SM. For inop ALS, increase LNAV/VNAV visibility all Cats to 1⅜ SM. Circling Rwy 24 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. Rwy 15 helicopter visibility reduction below RVR 4000 NA. For inop ALS when using Chatham altimeter setting, increase LNAV Cats A and B visibility to RVR 5500. **RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Chatham altimeter setting).

A

MALSR


MISSED APPROACH: Climb to 2000 direct BOWLE and on 096° track to COOKK and on 022° track to LFV VOR/DME and hold.


ATIS	BOSTON APP CON	HYANNIS TOWER ★	GND CON	UNICOM
123.8	118.2 284.6	119.5 (CTAF) 257.8	118.45	122.95



ELEV 54 D TDZE 54

4 NM Holding Pattern	2000	BOWLE	tr 096°	COOKK	tr 022°	LFV





CATEGORY	A	B	C	D
LPV DA**	254/24 200 (200-½)			
LNAV/VNAV DA	569/60 515 (600-1¼)			
LNAV MDA	600/40 546 (600-¾)		600/60 546 (600-1¼)	
CIRCLING	600-1 546 (600-1)		860-2¼ 806 (900-2¼)	860-2½ 806 (900-2½)

REIL Rwy 6
HIRL Rwys 6-24 and 15-33 L

NE-1, 01 OCT 2026 to 29 OCT 2026
NE-1, 01 OCT 2026 to 29 OCT 2026