

LOC I-RIW <u>110.5</u>	APP CRS 284°	Rwy Ldg TDZE Apt Elev	8204 5459 5516
----------------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 28
CENTRAL WYOMING RGNL (RIW)

T	NA	When local altimeter setting not received, use Lander altimeter setting: increase DA to 5713 feet; increase all MDA 60 feet and S-LOC 28 Cat C and D visibility ¼ mile. For inop MALSR, when using Lander altimeter setting, increase S-HLS 28 all Cts visibility to ¾ mile and S-LOC 28 Cat C and D visibility to 1¾ mile. VDP NA when using Lander altimeter setting.
---	----	--

MALSR



MISSED APPROACH: Climb to 6800 then climbing right turn to 7700 direct RIW VOR/DME and hold, continue climb-in-hold to 7700.

ASOS 121.425	SALT LAKE CENTER 133.25 285.6	UNICOM 122.8 (CTAF) L
-----------------	----------------------------------	---------------------------------

ALTERNATE MISSED APCH FIX

FETIK BOY

117.8 BOY

R-180

Chan 125

10.8

ELEV 5516	D	TDZE 5459
-----------	----------	-----------

REIL Rwy 1, 10 and 19 L

MIRL Rwy 1-19 **L**HIRL Rwy 10-28 **L**

FAF to MAP 6.

Knots	60	90	120	150	180
Min:Sec	6:54	4:36	3:27	2:46	2:18

RIVERTON, WYOMING

Amdt 3B 07SEP23

SALT LAKE CENTER
133.25 285.6

UNICOM
122.8 (CTAF) **L**

(IAF)
FETIK
RIW 14

BOYSEN RESERVOIR
117.8 BOY 
Chan 125

LOCALIZER 110.5
I-RW

RIVERTON
114.05 RIW ::-
Chan 87(Y)

(IAF)
HONOX

(IF/IAF)
DONVY IN
RIW 14

6800	7700	RIW
		

LIMNY INT
RIW 7.5

DONVY INT
RIW 14

One Minute Holding Pattern

	1.2	5.7 NM	6.5 NM	
CATEGORY	A	B	C	D
S-ILS 28	5659-1/2 200 (200-1/2)			
S-LOC 28	5880-1/2 421 (400-1/2)		5880-3/4 421 (400-3/4)	
CIRCLING	6000-1 484 (500-1)		6000-1 1/2 484 (500-1 1/2)	6120-2 604 (700-2)

CENTRAL WYOMING RGNL (RIW)

ILS or LOC RWY 28

43°04'N-108°28'W

NW-1, 01 OCT 2026 to 29 OCT 2026

NW-1, 01 OCT 2026 to 29 OCT 2026