

WAAS CH 90106 W12A	APP CRS 126°	Rwy Ldg TDZE Apt Elev	12R 8587 46 62	12L 8831 44 62
--	------------------------	-----------------------------	--	--

RNAV (GPS) Y RWY 12R

MINETA SAN JOSE INTL (SJC)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C (31°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to 1 mile and LNAV Cats C/D visibility to 1½ mile.

MALSR

Rwy 12R

MISSED APPROACH: Climb to 4600 direct H1VAK and on track 124° to GILRO and hold.

D-ATIS 126.95	NORCAL APP CON 120.1 290.25	SAN JOSE TOWER ★ 124.0 (CTAF) 0 257.6	GND CON 121.7	UNICOM 122.95
-------------------------	---------------------------------------	---	-------------------------	-------------------------

ELEV 62	D	TDZE 12R 46	TDZE 12L 44
---------	----------	-------------	-------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).				
ARTAQ		SUNNE		
1800		1800		
GP 3.00°		1800		
TCH 58		1800		
2 NM		4.1 NM		1.3 NM
CATEGORY	A	B	C	D
LPV DA	246-½ 200 (200-½)			
LNAV/VNAV DA	371-⅝ 325 (400-⅝)		371-1 325 (400-1)	
LNAV MDA	520-½ 474 (500-½)		520-1 474 (500-1)	
SIDESTEP 12L	520-1 476 (500-1)		520-1½ 476 (500-1½)	520-2 476 (500-2)

SAN JOSE, CALIFORNIA
Amdt 3A 21JUL16

37°22'N-121°56'W

MINETA SAN JOSE INTL (SJC)

RNAV (GPS) Y RWY 12R

SW-2, 01 OCT 2026 to 29 OCT 2026

SW-2, 01 OCT 2026 to 29 OCT 2026