

LOC/DME I-DEC	APP CRS	Rwy Ldg	8496
110.9	060°	TDZE	677
Chan 46		Apt Elev	682


ILS or LOC RWY 6
DECATUR (DEC)

⚠ When local altimeter setting not received, use Lincoln altimeter setting and increase S-ILS 6 DA to 957 feet; increase all MDAs 80 feet and S-LOC 6 visibility Cat C/D to RVR 6000 and Circling visibility Cat C/D ¼ SM. For inop ALS, increase S-LOC 6 Cat C/D visibility to 1 ½ SM. For inop ALS when using Lincoln altimeter, increase S-ILS all Cats visibility to RVR 4500. VDP NA when using Lincoln altimeter setting. * RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Lincoln altimeter setting).

MALSR
A5

MISSED APPROACH: Climb to 2200 then climbing left turn to 3100 on heading 270° and AXC VORTAC R-348 to MAROA INT/ AXC 14.3 DME and hold.

ATIS	CHAMPAIGN APP CON*	DECATUR TOWER*	GND CON	UNICOM
126.35	132.85 290.225	118.9 (CTAF) 0 291.775	121.75 291.775	122.95



ELEV 682 **D** TDZE 677

HIRL Rwy 6-24 1
MIRL Rws 12-30 and 18-36 1
FAF to MAP 4.3 NM

CATEGORY	A	B	C	D
S-ILS 6*	877/24 200 (200-½)			
S-LOC 6	1140/24	463 (500-½)	1140/50	463 (500-1)
CIRCLING	1140-1 458 (500-1)	1240-1 558 (600-1)	1360-2 678 (700-2)	1360-2¼ 678 (700-2¼)

Knots 60 90 120 150 180
Min:Seq 4:18 2:52 2:09 1:43 1:26

Remain within 10 NM

ELWIN LOM I-DEC 5.8

2200 3100 hdg 270° AXC R-348 MAROA INT

2200 060° 2091

GS 3.00° TCH 57

Use I-DEC DME when on the localizer course.

3.1 NM 1.2 NM

I-DEC 2.8 I-DEC 1.6

EC-3, 01 OCT 2026 to 29 OCT 2026

EC-3, 01 OCT 2026 to 29 OCT 2026