

WAAS CH 61102 W35A	APP CRS 354°	Rwy Ldg 6502 TDZE 868 Apt Elev 874
--	------------------------	---

RNAV (GPS) RWY 35

KALAMAZOO/BATTLE CREEK INTL (AZO)

RNP APCH - GPS.

⚠

Circling Rwy 5, 9, 17, 23, 27 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use BTL altimeter setting and increase LPV DA to 1112 feet; increase LNAV/VNAV DA to 1308 and all visibilities to RVR 4000. Increase all MDAs 60 feet and LNAV visibility Cats C and D to RVR 5000 and Circling visibility Cats C and D ¼ SM. Baro-VNAV and VDP NA when using BTL altimeter setting. For inop ALS when using BTL altimeter setting, increase LNAV Cats C and D visibility to 1 ½ SM. * RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using BTL altimeter setting).

MALSR

MISSED APPROACH:
Climb to 3000 direct
OSEGO and hold.

ATIS 127.25	GREAT LAKES APP CON * 121.2 239.25	KALAMAZOO TOWER * 118.3 (CTAF) 0 257.875	GND CON 121.9	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------

