

VOR RWY 9
WITTMAN RGNL (OSH)

MISSED APPROACH: Climb to 3000 on OSH VOR/DME R-111 to LEWKO INT/OSH 15.1 DME and hold.

Diagram illustrating the CEOL VORTAC and associated navigation aids. The diagram shows the CEOL VORTAC (2.6 MHz) and OSH VOR/DME (2.1 MHz) stations. The CEOL VORTAC has a 270° radial and a 090° radial. The OSH VOR/DME has a 2.84° TCH 50. The diagram also shows the CEOL FIX MINIMUMS (DME REQUIRED) table.

CATEGORY	A	B	C	D
S-9	1420-1	622 (700-1)	1420-1 ³ / ₄	622 (700-1 ³ / ₄)
CIRCLING	1420-1	611 (700-1)	1420-1 ³ / ₄ 611 (700-1 ³ / ₄)	1440-2 631 (700-2)

CEOL FIX MINIMUMS (DME REQUIRED)

CATEGORY	A	B	C	D
S-9	1280-1	482 (500-1)	1280-1 ³ / ₈	482 (500-1 ³ / ₈)
CIRCLING	1280-1 471 (500-1)	1300-1 491 (500-1)	1360-1 ¹ / ₂ 551 (600-1 ¹ / ₂)	1440-2 631 (700-2)

Diagram also shows the CEOL FIX MINIMUMS (DME REQUIRED) table. The table has four columns: CATEGORY, A, B, C, and D. The rows are S-9 and CIRCLING. The S-9 row shows 1280-1, 482 (500-1), 1280-1 3/8, and 482 (500-1 3/8). The CIRCLING row shows 1280-1, 1300-1, 1360-1 1/2, and 1440-2.

EC-3, 01 OCT 2026 to 29 OCT 2026

EC-3, 01 OCT 2026 to 29 OCT 2026