

APP CRS	Rwy Ldg	8394
276°	TDZE	7
	Apt Elev	65

RNAV (RNP) Z RWY 28R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP AR APCH - GPS. RADAR required.

Simultaneous approach authorized. For uncompensated Baro-VNAV systems, procedure NA below 7°C or above 54°C. For inop ALS, increase RNP 0.15 visibility to RVR 5500 and increase RNP 0.30 visibility to 1¾ SM.

MALSR

AS

MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct HUKUK and hold, continue climb-in-hold to 4000.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4
-----------------	--------------------------------	--------------------------------------	------------------

MISSED APCH FIX
4 NM
307°
127°
HUKUK

276°
RW28R
276°
(6.1)
2000
276°
(6.3)
2500
233°
(5.6)
2500
153°
(5.3)
4000
096°
(3.2)
210K
5000
(IF) JENPO
CUSRA
PRHIB
(FAF) SNAPE
(IF) HUXIM
4000
210K
(IF) FUZZY
4000
290°
(9.2)
(IAF) CRNWL
5000
MSA RW28R 25 NM
2100

ELEV 65 TDZE 7

800
4000
HUKUK

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

See planview for multiple IF locations.

276°
RW28R
2000
SNAPE
2000
GP 3.00°
TCH 49

6.1 NM

CATEGORY	A	B	C	D
RNP 0.15 DA		362/40	355 (300-¾)	
RNP 0.30 DA		618-1⅜	611 (600-1⅜)	

AUTHORIZATION REQUIRED

FORT LAUDERDALE, FLORIDA
Amdt 2 12AUG21

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)
26°04'N-80°09'W

RNAV (RNP) Z RWY 28R