

VORTAC HNL	APP CRS	Rwy Ldg	7989
114.8	074°	TDZE	17
Chan 95		Apt Elev	32

VOR RWY 4R

KALAELOA (JOHN RODGERS FLD) (JRF)(PHJR)

DME required.


▼

⚠

Circling NA north of Rwy 4R-22L. Rwy 4R helicopter visibility reduction below ¾ SM NA. VDP NA when using HNL/PHNL altimeter setting. When local altimeter not received, use HNL/PHNL altimeter setting and increase all MDAs 40 feet and S-4R visibility Cat C/D ½ SM, and Circling visibility Cat C ½ SM.

MISSED APPROACH: Climbing right turn to 3000 on heading 248° and HNL VORTAC R-241 to GECKO/HNL 22.4 DME and hold.

ATIS	HCF APP CON	KALAELOA TOWER ★	GND CON
119.8	118.3 269.0	132.6(CTAF) 0 340.2	123.8 336.4



	TARLE HNL 22.4	HPKNS HNL 13.4	YUDYU HNL 8.4	GECKO HNL 22.4
	3000	1700	3000	
	074°	3.06° TCH 55	hdg 248°	
	9 NM	3.5 NM	1.5 NM	
CATEGORY	A	B	C	D
S-4R	560-1 543 (600-1)		560-1⅝ 543 (600-1⅝)	560-1¾ 543 (600-1¾)
CIRCLING	560-1 528 (600-1)		560-1⅝ 528 (600-1⅝)	600-2 568 (600-2)

