

WAAS CH 82108 W19A	APP CRS 191°	Rwy Ldg TDZE 995 Apt Elev 1027
--	------------------------	--

RNAV (GPS) Y RWY 19L

KANSAS CITY INTL (MCI)



RNP APCH - GPS.

▼ Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats and LNAV Cats C/D visibility to RVR 5500. Simultaneous approach authorized except from BUDIE and FARMS.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 4000 direct ANX VORTAC and hold.

D-ATIS 128.375	KANSAS CITY APP CON 120.95 318.1	INTERNATIONAL TOWER 128.2 254.25	GND CON 121.8	CLNC DEL 135.7	CPDLC
--------------------------	--	--	-------------------------	--------------------------	-------



CATEGORY		A	B	C	D
LPV	DA	1195/18		200 (200-½)	
LNAV/VNAV	DA	1365/35		370 (400-⅝)	
LNAV	MDA	1360/24	365 (400-½)	1360/35	365 (400-⅝)
CIRCLING		1540-1	513 (600-1)	1540-1½ 513 (600-1½)	1580-2 553 (600-2)