

LOC I-AWO	APP CRS	Rwy Ldg	5332
111.5	342°	TDZE	135
		Apt Elev	142

LOC RWY 34

ARLINGTON MUNI (AWO)


ADF required. When local altimeter setting not received, use Whidbey Island NAS (Ault Field) altimeter setting: increase all MDA 80 feet and visibility S-34 Cats C and D and Circling Cats B and C ¼ SM. For inop MALS, increase S-34 Cats C and D visibility to 1 3⁄8 .

MALS

A₂

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct WATON LOM and hold.

AWOS-3PT 135.625	SEATTLE APP CON 128.5 306.9	CTAF 122.725 0
---------------------	--------------------------------	-------------------



Remain within 10 NM

AW LOM 6000

162°

2000

342°

1700

3.05° TCH 46

4.7 NM

CATEGORY	A	B	C	D
S-34	580-3⁄4	445 (500-3⁄4)	580-1	445 (500-1)
CIRCLING	840-1 698 (700-1)	900-1 758 (800-1)	1000-2½ 858 (900-2½)	1040-3 898 (900-3)

ELEV 142 TDZE 135

MIRL Rwy 16-34
REIL Rwy 16
REIL Rws 11 and 29

FAF to MAP 4.7 NM

Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34