


WAAS CH 61221 W13A	APP CRS 133°	Rwy Idg TDZE 125 Apt Elev 125	5007
--	------------------------	---	-------------

RNAV (GPS) RWY 13


LUMBERTON RGNL (LBT)

RNP APCH-GPS.	MISSED APPROACH: Climb to 3000 direct NECIR and on track 110° to COTUB and hold.
Rwy 13 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Maxton altimeter setting; increase all MDAs 60 feet; increase LP Cat C and Circling Cat C visibility ¼ SM and LNAV Cat C ½ SM. Straight-in Rwy 13 NA at night, Circling Rwy 13, 31 NA at night.	

ASOS 134.775	FAYETTEVILLE APP CON 133.0 290.25	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



4 NM Holding Pattern	CUUBE	3000	NECIR	tr 110°	COTUB
2300	313°	133°	133°	1900	700
	4 NM	3.7 NM	1.7 NM		
CATEGORY	A	B	C	D	
LP MDA	500-1 375 (400-1)				NA
LNAV MDA	600-1 475 (500-1)		600-1 475 (500-1)		NA
CIRCLING	660-1 535 (600-1)		720-1 595 (600-1)		NA



SE-2, 01 OCT 2026 to 29 OCT 2026

SE-2, 01 OCT 2026 to 29 OCT 2026