

WAAS	APP CRS	Rwy Idg	5343
CH 97421	053°	TDZE	124
W05A		Apt Elev	125

RNAV (GPS) RWY 5

LUMBERTON RGNL (LBT)

RNP APCH - GPS.


▼

▲

When local altimeter setting not received, use Maxton altimeter setting: increase LPV DA to 383 feet; LNAV/VNAV DA to 594 feet and all visibility ¼ SM; increase all MDAs 60 feet and LNAV visibility Cat C and Circling Cat C ¼ SM. Baro-VNAV and VDP NA when using Maxton altimeter setting. Circling Rwy 13, 31 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MISSED APPROACH:
Climb to 2000 direct
WIVGA and hold.

ASOS 134.775	FAYETTEVILLE APP CON 133.0 290.25	UNICOM 122.8 (CTAF) 0
-----------------	--------------------------------------	--------------------------



ELEV 125		TDZE 124	
UMABY		AXJAB	
2200		1900	
Procedure Turn NA		HUNOP 1.7 NM to RW05	
GP 3.00°		* 1.1 NM to RW05	
TCH 60		RW05	
4.6 NM		3.7 NM	
CATEGORY A		CATEGORY B	
LPV DA		327-¾ 203 (300-¾)	
LNAV/VNAV DA		538-1⅞ 414 (500-1⅞)	
LNAV MDA		520-1 396 (400-1)	
CIRCLING		720-1½ 595 (600-1½)	

2000

WIVGA

* LNAV only.

13

31

5007 ft

5505 x 150

053°

MIRL Rwy 5-23 0
REIL Rws 5 and 23 0