

APP CRS
105°

Rwy Ldg
TDZE
143

9953
Apt Elev
143

RNAV (RNP) Z RWY 10

BALTIMORE/WASHINGTON INTL THURGOOD MARSHALL (BWI)

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -11°C or above 54°C. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 4500, increase RNP 0.30 all Cats visibility to 1½ SM.

ALSF-2
A

MISSED APPROACH:
Climb to 2500 on track 105° to HURTZ and hold.


D-ATIS
115.1 127.8

119.0 282.275
124.55 317.425

POTOMAC APP CON
(020°-100°) **119.7 290.475** (131°-180°)
(101°-130°) **128.7 307.9** (181°-019°)

BALTIMORE TOWER
119.4 257.8

GND CON
121.9



JEANS
1500

1500

GP 3.00°
TCH 55

105°

See planview for multiple IF locations.

4.1 NM

RW10

2500
tr 105°

HURTZ

CATEGORY	A	B	C	D
RNP 0.11 DA		444/24	301 (400-½)	
RNP 0.30 DA		628/50	485 (500-1)	

AUTHORIZATION REQUIRED

ELEV 143

D

TDZE 143

TDZL/RCLS Rwy's 10 and 33L
REIL Rwy's 15L and 33R
HIRL all rwy's