

WAAS CH 82008 W28A	APP CRS 280°	Rwy Ldg 8003 TDZE 196 Apt Elev 201
--	------------------------	---

RNAV (GPS) RWY 28

LAKE CITY GATEWAY (LCQ)


RNP APCH-GPS.

▼ Baro-VNAV and VDP NA when using Gainesville altimeter setting. For uncompensated Baro-VNAV systems, UNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use Gainesville altimeter setting: Increase LPV DA to 624 feet and all visibility ¼ SM; UNAV/VNAV DA to 640 feet and all visibility ⅓ SM; increase all MDAs 100 feet and UNAV visibility Cat C and D ¼ SM and Circling visibility Cat C ½ SM and Circling Cat D ¼ SM. Circling Rwy 10 NA at night.

▲ Rwy 13 helicopter visibility reduction below ⅓ SM NA.

MISSED APPROACH:
Climb to 2000 direct
JTUX and hold.

AWOS-3 120.675	JACKSONVILLE CENTER 125.375 254.325	LAKE CITY TOWER ★ 119.2 (CTAF) 0 314.6	GND CON 121.9	UNICOM 122.95
-------------------	--	---	------------------	------------------



CATEGORY	A	B	C	D
LPV DA		540-1	344 (400-1)	
LNNAV/VNAV DA		556-1	360 (400-1)	
LNNAV MDA	640-1	444 (500-1)	640-1 $\frac{3}{8}$	444 (500-1 $\frac{3}{8}$)
CIRCLING	760-1	559 (600-1)	780-1 $\frac{1}{2}$ 579 (600-1 $\frac{1}{2}$)	960-2 $\frac{1}{2}$ 759 (600-2 $\frac{1}{2}$)

LAKE CITY, FLORIDA
Amdt 1C 15JUL21

LAKE CITY GATEWAY (LCQ)

RNAV (GPS) RWY 28

30°11'N-82°35'W

SE-3, 01 OCT 2026 to 29 OCT 2026