

WAAS
CH **86519**
W05A

APP CRS
053°

Rwy Ldg
TDZE **1297**
Apt Elev **1297**

RNAV (GPS) RWY 5

MANSFIELD LAHM RGNL (MF'D)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F).

MISSED APPROACH: Climb to 3000 direct NANNI and hold.

ATIS
125.3

CLEVELAND APP CON ★
128.35 360.65

MANSFIELD TOWER ★
119.8 (CTAF) 291.775

GND CON
121.8 291.775

UNICOM
122.95

The main approach chart for RNAV (GPS) RWY 5 at Mansfield, Ohio. It shows the following waypoints and distances:

- DUSKY to HUDOR: 3000, 120°, (20.8)
- HUDOR to JOKAM: 3000 NoPT, 143°, (6.3)
- JOKAM to ZOLEL: 053°, 233°, 3000 NoPT, (6.3)
- ZOLEL to YOGUD: 053°, 2700, 053°, 161
- YOGUD to WOVOM: 3000 NoPT, 323°, (6.3)
- WOVOM to RW05: 2.3 NM
- Distance from RW05 to NANNI: 1564

A missed approach fix is shown at NANNI, 4 NM from the end of the runway. A Minimum Safe Altitude (MSA) circle for RW05 is shown with a 3000 ft ceiling. The chart also includes a 4 NM holding pattern at JOKAM.

4 NM Holding Pattern JOKAM

3000

233°

053°

GP 3.00°

TCH 50

2700

053°

2060

6 NM

2 NM

0.8

1.5 NM

WOVOM 2.3 NM to RW05

*1.5 NM to RW05

RW05

*LNAV only.

ELEV 1297

TDZE 1297

CATEGORY	A	B	C	D
LPV DA	1547-7/8		250 (300-7/8)	
LNAV/VNAV DA	1590-1		293 (300-1)	
LNAV MDA	1820-1	523 (600-1)	1820-1½	523 (600-1½)
CIRCLING	1820-1	523 (600-1)	2000-2 703 (800-2)	2000-2¼ 703 (800-2¼)

HIRL Rwy 5-23 and 14-32

REIL Rwy 5 and 23

MANSFIELD, OHIO
Amtd 1A 13SEP18

40°49'N-82°31'W

MANSFIELD LAHM RGNL (MF'D)
RNAV (GPS) RWY 5

EC-2, 01 OCT 2026 to 29 OCT 2026

EC-2, 01 OCT 2026 to 29 OCT 2026