

|                                              |                        |                                                             |
|----------------------------------------------|------------------------|-------------------------------------------------------------|
| VORTAC LFT<br><b>109.8</b><br>Chan <b>35</b> | APP CRS<br><b>137°</b> | Rwy Ldg <b>5403</b><br>TDZE <b>42</b><br>Apt Elev <b>42</b> |
|----------------------------------------------|------------------------|-------------------------------------------------------------|

VOR/DME RWY 11

LAFAYETTE RGNL/PAUL FOURNET FLD (LFT)



Procedure NA at night. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Acadiana Rgnl altimeter setting and increase all MDAs 40 feet. increase Circling visibility Cat C/D  $\frac{1}{4}$  SM.

**MISSED APPROACH:** Climb to 2100 to LFT VORTAC and on LFT VORTAC R-092 to LULEW/LFT 16 DME.

|                |                                    |                                           |                  |                  |
|----------------|------------------------------------|-------------------------------------------|------------------|------------------|
| ATIS<br>134.05 | LAFAYETTE APP CON ★<br>121.1 363.0 | LAFAYETTE TOWER ★<br>118.5 (CTAF) 0 257.8 | GND CON<br>121.8 | UNICOM<br>122.95 |
|----------------|------------------------------------|-------------------------------------------|------------------|------------------|

