

LOC/DME I-RAP
109.3
Chan **30**

APP CRS
324°

Rwy Ldg
TDZE
Apt Elev
8701
3160
3204

ILS or LOC RWY 32

RAPID CITY RGNL (RAP)

⚠

⚠

DME and RNAV 1-GPS required. ILS glideslope unusable for coupled approaches below 3360. For inop ALS, increase S-ILS Cat E visibility to RVR 4000 and S-LOC Cat E visibility to 1½ SM. # RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3700 then climbing right turn to 5500 direct HELTA and hold.

ASOS 118.525	ELLSWORTH APP CON ★ 119.5 259.1	RAPID CITY TOWER ★ 125.85 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------

RNAV 1-GPS or RADAR REQUIRED

ELEV 3204 **D** TDZE 3160

3700	5500	HELTA I-RAP 13.3	Use I-RAP DME when on the LOC course.		
*LOC only.			YAVUC I-RAP 7.3	HELTA I-RAP 13.3	One Minute Holding Pattern
*I-RAP 2.9			5000	5000	5500
I-RAP 1.6			1.3 NM	4.4 NM	6 NM
GS 3.00° TCH 54					
CATEGORY	A	B	C	D	E
S-ILS 32#	3360/24 200 (200-½)				
S-LOC 32	3620/24	460 (500-½)	3620/45	460 (500-¾)	
CIRCLING	3660-1 456 (500-1)	3840-1 636 (700-1)	3860-1¾ 656 (700-1¾)	3940-2¼ 736 (800-2¼)	3960-2¾ 756 (800-2¾)

RAPID CITY, SOUTH DAKOTA

Amdt 21A 07DEC17

44°03'N-103°03'W

RAPID CITY RGNL (RAP)

ILS or LOC RWY 32