

WAAS CH 40433 W23A	APP CRS 234°	Rwy Ldg TDZE Apt Elev	3601 3204 3204
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 23


RAPID CITY RGNL (RAP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Ellsworth AFB altimeter setting and increase all DA 25 feet and all MDA 40 feet. VDP and Baro-VNAV NA when using Ellsworth AFB altimeter setting.

MISSED APPROACH: Climbing left turn to 5300 direct EWEBU and hold.

ASOS 118.525	ELLSWORTH APP CON ★ 119.5 259.1	RAPID CITY TOWER ★ 125.85 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------



5300 EWEBU		YUKUR 4800		EWEBU 4800		4 NM Holding Pattern	
*LNAV only.		NULIY 1.9 NM to RWY 23		*1 NM to RWY 23		GP 3.00° TCH 38	
RWY 23		3820*		234°		054°	
1 NM		0.9 NM		3 NM		4 NM	
CATEGORY	A	B	C	D			
LPV DA	3454-1	250 (300-1)	NA				
LNAV/VNAV DA	3454-1	250 (300-1)	NA				
LNAV MDA	3560-1	356 (400-1)	NA				
CIRCLING	3660-1 456 (500-1)	3840-1 636 (700-1)	NA				

ELEV 3204 D TDZE 3204