

WAAS CH 93717 W32A	APP CRS 324°	Rwy Ldg TDZE Apt Elev	8701 3160 3204
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32
RAPID CITY RGNL (RAP)



⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C (-11°F) or above 51°C (125°F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats to RVR 4500 and LNAV Cat E to 1½ SM. # RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR



MISSED APPROACH: Climb to 3700 then climbing right turn to 5500 direct HELTA and hold.

ASOS 118.525	ELLSWORTH APP CON ★ 119.5 259.1	RAPID CITY TOWER ★ 125.85 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------



3700		5500		HELTA				
								
* LNAV only								
								
RW32		1.3 NM		4.4 NM		6 NM		
		* 1.3 NM to RW32		YAVUC 5000		HELTA 5000		
				324°		144°		
				5000		5 NM Holding Pattern		
						GP 3.00°		
						TCH 54		
CATEGORY	A		B		C		D	E
LPV DA#			3360/24		200 (200-½)			
LNAV/VNAV DA			3410/24		250 (300-½)			
LNAV MDA	3620/24		460 (500-½)		3620/45		460 (500-¾)	
CIRCLING	3660-1 456 (500-1)		3840-1 636 (700-1)		3860-1¾ 656 (700-1¾)		3940-2¼ 736 (800-2¼)	
							3960-2¾ 756 (800-2¾)	

NC-1, 01 OCT 2026 to 29 OCT 2026

NC-1, 01 OCT 2026 to 29 OCT 2026