

APP CRS	Rwy Ldg	9007
020°	TDZE	2966
	Apt Elev	2977

RNAV (RNP) Y RWY 2
GLACIER PARK INTL (GPI)

RF and GPS required. Missed approach requires RNP less than 1.0.
For uncompensated Baro-VNAV systems, procedure NA below -21°C (-5°F) or above 43°C (109°F). For inoperative MALSR increase RNP 0.10* visibility to 1¼ and RNP 0.30 visibility to 2.
*Missed approach requires minimum climb of 220 feet per NM to 6100.

MALSR
A5

MISSED APPROACH: Climb to 10000 via left turn to JOGAD, and via left turn to ROYOG and via left turn to TONUJ, and via 121° track to WILTO and via 129° track to ANGL and hold.

ATIS 132.625	SALT LAKE CENTER 127.075 244.875	GLACIER TOWER ★ 124.55 (CTAF) 0	GND CON 121.6	UNICOM 122.95
-----------------	-------------------------------------	------------------------------------	------------------	------------------



ELEV 2977 D TDZE 2966

TWR 3510 X 75
9007 X 150

REIL Rwy 20 0
MIRL Rwy 12-30 0
HIRL Rwy 2-20 0

Procedure Turn Turn NA		JUNRU		WULEX		AVDIH		10000 		JOGAD 		ROYOG 	
8000		015°		7200		020°		BINGQ 5200		RW02			
GP 3.00° TCH 51				6200		5200							
		3 NM		3.2 NM		7.1 NM		6.7 NM					
CATEGORY		A		B		C		D					
RNP 0.10 DA*		NA		3340-¾		374 (400-¾)							
RNP 0.30 DA		NA		3522-1½		556 (600-1½)							
AUTHORIZATION REQUIRED													

NW-1, 01 OCT 2026 to 29 OCT 2026

NW-1, 01 OCT 2026 to 29 OCT 2026