

WAAS CH 93512 W32A	APP CRS 321°	Rwy Ldg TDZE 518 Apt Elev 543
--	------------------------	---

RNAV (GPS) RWY 32

SMYRNA (MQY)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALS when using Nashville Intl altimeter setting, increase LNAV/VNAV all Cats visibility to 1 3⁄8 mile. When local altimeter setting not received, use Nashville Intl altimeter setting and increase LPV DA to 749 feet, LNAV/VNAV DA to 998 feet, and all MDA 40 feet; increase LNAV Cats C/D visibility 1⁄8 mile and increase Circling Cat C visibility 1⁄4 mile. Baro-VNAV and VDP NA when using Nashville Intl altimeter setting.

MALS

MISSED APPROACH:

Climb to 1500 then climbing right turn to 3000 direct JOPIV and hold.

AWOS-3PT 119.125	NASHVILLE APP CON 118.4 360.7	SMYRNA TOWER★ 118.5 (CTAF) 0 233.1	GND CON 121.4	UNICOM 122.95
----------------------------	---	--	-------------------------	-------------------------

ELEV **543** TDZE **518**

REIL Rwy 14

HIRL Rwy 14-32

MIRL Rwy 1-19

REIL Rwys 1, 19, and 32

1500 3000 JOPIV

↑

↷

✧

*LNAV only

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 57).

4 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	718-1⁄2		200 (200-1⁄2)	
LNAV/VNAV DA	967-1		449 (500-1)	
LNAV MDA	960-1⁄2	442 (500-1⁄2)	960-7⁄8	442 (500-7⁄8)
CIRCLING	1100-1 557 (600-1)	1200-1 657 (700-1)	1260-2 717 (800-2)	1480-3 937 (1000-3)

GP 3.00° TCH 51

SMYRNA, TENNESSEE
Amdt 1A 20AUG15

36°01'N-86°31'W

SMYRNA (MQY)

RNAV (GPS) RWY 32

SE-1, 01 OCT 2026 to 29 OCT 2026

SE-1, 01 OCT 2026 to 29 OCT 2026