

LOC/DME I-OOS 111.55 Chan 52 (Y)	APP CRS 095°	Rwy Ldg TDZE Apt Elev 5000 39 55
--	------------------------	--


ILS or LOC RWY 9R
ORLANDO SANFORD INTL (SF'B)

⚠ When local altimeter setting not received, use Orlando Exec altimeter setting and increase S-ILS DA to 282, and all MDA 60 feet; increase S-LOC 9R Cat C, D visibility ¼ mile, Circling Cat C visibility ½ mile and JOSKA Fix Minimums S-LOC 9R Cats C, D visibility ¼ mile. Simultaneous approach authorized with Rwy 9L. Night landing: Rwy 27C NA.

MALSR

MISSED APPROACH: Climb to 500 then climbing right turn to 2800 on heading 125° and ORL VORTAC R-070 to MALET INT/ORL 26.2 DME and hold.

ATIS 125.975	ORLANDO APP CON 135.3 351.9 (N) 125.225 351.9 (S)	SANFORD TOWER ★ 120.3 (CTAF) 0 254.35	GND CON 121.35 254.35
------------------------	---	---	---------------------------------



	ELEV 55	TDZE 39
	One Minute Holding Pattern	JOSKA I-OOS 2.5
	GS 3.00° TCH 45	I-OOS 0.9
	2000	*600 when using Orlando Exec altimeter setting.
	275°	JOSKA I-OOS 2.5
	095°	I-OOS 0.9
	095°	
	1600	
	7 NM	
	3.2 NM	
	1.6 NM	
CATEGORY	A	B
S-ILS 9R	239-½	200 (200-½)
S-LOC 9R	540-½	501 (500-½)
CIRCLING	580-1	525 (600-1)
	545 (600-½)	640-2
	585 (600-2)	
	JOSKA FIX MINIMUMS (DME REQUIRED)	
S-LOC 9R	440-½	401 (400-½)
CIRCLING	580-1	525 (600-1)
	545 (600-½)	640-2
	585 (600-2)	
	FAC to MAP 4.8 NM	
	Knots	60 90 120 150 180
	Min:Sec	4:48 3:12 2:24 1:55 1:36

SE-3, 01 OCT 2026 to 29 OCT 2026

SE-3, 01 OCT 2026 to 29 OCT 2026