


WAAS CH 69400 W31A	APP CRS 312°	Rwy Ldg TDZE 1062 Apt Elev 1076
--	------------------------	---

RNAV (GPS) RWY 31


DUBUQUE RGNL (DBQ)


RNP APCH - GPS.		MALSR 	MISSED APPROACH: Climb to 2800 direct HULOT and hold.
 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LPV all Cats visibility to 1½ SM and LNAV Cats C/D visibility to 1¾ SM.			

ATIS 127.25	CHICAGO CENTER 133.95 281.4	DUBUQUE TOWER★ 119.5 (CTAF) 0 254.4	GND CON 121.8	UNICOM 122.95
-----------------------	---------------------------------------	---	-------------------------	-------------------------



ELEV 1076	D	TDZE 1062
-----------	----------	-----------



2800 HULOT		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 57).		JIPDA 4 NM Holding Pattern	
		RIPOC 2700		6000 3100	
1.4 NM to RW31		312°		GP 3.00° TCH 50	
1.4 NM		3.5 NM		6.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1481-¾		419 (500-¾)		
LNAV/VNAV DA	1580-1		518 (600-1)		
LNAV MDA	1580-½ 518 (600-½)		1580-1 518 (600-1)		
CIRCLING	1620-1 544 (600-1)		1620-1½ 544 (600-1½)		1800-2¼ 724 (800-2¼)

NC-3, 01 OCT 2026 to 29 OCT 2026

NC-3, 01 OCT 2026 to 29 OCT 2026